

VISCOM - INK-JET DIGITAL

Issue date : 25/01/2016
Date last modification : 25/01/2016**08992 - RI-DOT MATT WHITE PVC WK135 PTD GREY****Face Material**

Matt white monomeric vinyl film.

Type	Monomeric vinyl		
Colour and Finish	Matt white		
Weight	134 g/m ² ±10%	ISO-536	
Thickness	100 µ ±10%	ISO 534-80	

Adhesive

Acrylic permanent adhesive featuring dot pattern effect designed for short term bubble free indoor applications with excellent removability.

Reference	AP permanent
Type	Acrylic permanent
Min. Appl. Temp.	+10°C
Service Temp.	-30°C/+120°C
Shear	Medium
Tack	Medium N/inch ²
Final Adhesion	High N/inch

Liner

Type	One side siliconised clay coated Kraft		
Colour and Finish	White		
Weight	135 g/m ² ±10%	PP-032 - ISO 536	
Thickness	145 µ ±10%	ISO 534	
Transparency	n.a. %	DIN 53 147-64	

Applications

Short term bubble free indoor applications with excellent removability.
Testing between substrate and adhesive recommended prior to use.
Not recommended for wet applications.

Printing Methods

Gives excellent print results with UV, solvent, eco-solvent & latex ink-jet printing.
Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.
All information is subject to change without prior notice.

